



DIN EN 853 2 SN

Wire Braid Hydraulic Hose meets or exceeds DIN EN 853 2 SN, SAE 100R2 and ISO 1436 2SNR2



HOSE :

Tube	Synthetic rubber, resistant against hydraulic fluids (HL, HLP, HLPD, HVLP, HFA, HFAS, HFB, HFC)
Reinforcement	Two braids of high tensile steel wire
Cover	Abrasion and ozone resistant synthetic rubber Note: various covers available
Temperature range	-40 rC to 100 rC / -40 rF to +212 rF (max 120 rC/248 rF intermittent)
Standard branding	embossed

SEMPERIT  DIN EN 853 2SN DN 10 WP 330 BAR SAE100 R2S 3/8" 4785 PSI . Q . . W . . z 

Nominal Ø		Inside Ø	Braid Ø	Outside Ø	Working pressure		Test pressure	Burst pressure	Bend radius	Weight
mm	inch	mm	mm	mm	bar	psi	bar	bar	mm	kg/m
6	1/4	6,6	12,4	14,4	400	5800	800	1600	100	0,31
8	5/16	8,3	14,0	16,0	350	5075	700	1400	115	0,37
10	3/8	9,9	16,4	18,4	330	4785	660	1320	130	0,44
12	1/2	13,0	19,4	21,4	275	4000	550	1100	180	0,53
16	5/8	16,4	22,6	24,6	250	3625	500	1000	200	0,66
19	3/4	19,5	26,6	28,6	215	3120	430	850	240	0,84
25	1	26,0	34,5	37,1	165	2395	325	660	300	1,23
31	1-1/4	32,5	43,9	46,7	125	1815	250	500	420	1,77
38	1-1/2	38,7	51,1	54,5	90	1305	180	360	500	2,17
51	2	51,1	62,9	66,7	80	1160	160	320	630	2,79